



## KEY ADVANTAGES

- One size covers two wattage 40 | 60 W, simplifying inventory and installation planning
- Modular design, easy and quick installation
- Streamlined appearance
- Universal optics of 110°
- High visual comfort
- No hazardous materials
- Fast ROI thanks to long life span and reduced maintenance
- Can be linkable, allows for continuous, uninterrupted lighting across long spans, ideal for large or extended spaces

## TYPES OF APPLICATION

- Supermarkets
- Retail stores
- Office
- Parking
- Workshops

**5 YEARS  
WARRANTY**

**IP20**

**CR180**

**3000K**

**4000K**


**5000K**

## GENERAL INFORMATION

Nominal voltage	AC 220-240V
Electrical class	I class
Safety features	Open circuit protection, short circuit protection, overvoltage protection
Surge protection options (kV)	1KV-Line-Line   1KV-Line-Earth
Power factor (at full load)	0.9
Withstand voltage	3.0KV 60S 10mA
Power	40   60 W
LED Type	SMD2835
Reflector	Optics
Beam Angle	110°
Color Temperature	3000K   4000K   5000K   5700K   6500K
Color Rendering Index (Ra)	CRI >80
Efficacy	140-160 lm/W
Power Efficiency	≥85%
Start Time	≤0.2 s
Warm-up time to 60%	0.5 s
Housing	Aluminum
Housing finish	Electrostatic polyester powder coating
Standard color(s)	Black (RAL 9017)
Tightness level	IP20
Operating temperature range (Ta)	from -30°C to + 45°C
Operating Humidity	10-90%RH
Recommended installation height	from 2 to 4 m
Mounting Option	Hanging   surface
Sizes	1428x74x46 mm
Warranty	5 years

Lamp switch must control L line or control L and N lines.

## LIGHT DISTRIBUTIONS



110°